



Grommes~Precision Precision Electronics



DESIGNED AND
MADE IN U.S.A.



The AXIOM-G Series Power Amplifiers

1.5 Input* Channel Mixer Amplifier: 60, 125, 250, or 500 Watts of Continuous RMS Power

Living up to its name, the **AXIOM Amplifiers** provides the solid foundation in which to build an exceptional sound system. At only 2U high, the **AXIOM Amplifiers** is a high fidelity commercial audio amplifier that pumps 60/125/250/500 watts of continuous RMS power direct into 4-8 ohm or transformer isolated 25V and 70.7V lines, AX500G-OTL 70.7 volt only.


Engineered for all-in-one telephone paging solutions, the **AXIOM Series** includes a balanced 600 ohm/Tel-Page input (tamper resistant) that is capable of muting (defeatable) two aux inputs, which are strapped in parallel. It's packed with safeguards to ensure long-life, including: short circuit, peak overload, current limiting, thermal runaway, and output relay (no "pop" noises when turned on). Plus, with over a half-century of experience in the industry, **Grommes~Precision** backs the **AXIOM Series** with its unbeatable expertise and Assurance Pledge: a **7 year warranty** and a **30 day money back guarantee**.

An outstanding sound system needs an outstanding amplifier at its core. The **AXIOM Series**, which combines power, performance, protection, and dependability, is the **AXIOM** on which to build your outstanding sound system.

FEATURES

- Commercial Industrial Grade
- Independent 600 ohm/Tel-Page Input*
- Automatic Voice Activated Aux Muting (Defeatable)
- Built Tough: Multiple Protections Including Relay, Current Limit, Short Circuit, & A/C Circuit Breaker
- Heavy Duty Power Supply Designed for Continuous Operation
- 25V & 70.7 Built-in Output Transformer. (OTL Straight 70V.7V)
- Rack Mount Standard, Slim 2U Rack Design
- Convection Cooled—Reliable "No Maintenance" Design
- 7 Year Warranty & 30 Day Money Back Guarantee

	AX 60 / AX 125 / AX250 / AX500
POWER OUTPUT	60 /125/250/500 Watts Continuous RMS
MIXING CHANNELS	1.5
DISTORTION @RPO	≤0.1%
OUTPUTS	4-8 ohm / 25V-70.7V (70.7 only OTL)
FREQUENCY RESPONSE DIRECT	+/-1dB 20-20kHz
LINE	+/-1dB 50-15kHz
INPUTS	2-AUX IN PARALLEL; 1-600 ohm/TEL-PAGE
RACK UNITS	2U
DIMENSIONS / WEIGHT	19"Wx3.5"Hx11"D / 12 / 16 / 20 / 25LBS



Grommes~Precision

847-599-1799 · 800-SINCE-46 · FAX: 847-599-6178



1331 Estes Ave. · Gurnee, IL 60031 · USA

www.grommesprecision.com

Grommes~Precision



Grommes~Precision Precision Electronics



AXIOM 125 shown

AXIOM Series Amplifiers Architects Specifications

The power amplifier shall be a Grommes-Precision Electronics, Inc. model AXIOM 60G / 125G / 250G / 500G / 500G-OTL. The power amplifier shall provide 60/125/250/500 watts of continuous, monaural RMS power into a direct coupled 8 ohm, 25V, or 70.7V lines. The 25V and 70.7V output shall be supplied through a fully isolated output transformer. Total harmonic distortion at rated output shall be less than or equal to 0.15%. The frequency response for 8 ohm output shall be 20Hz to 20kHz, +0 to -1 dB. The frequency response for 25V and 70.7V output shall be 50Hz to 15kHz, +0 to -1dB. Hum and noise shall be at least 90dB below rated output unweighted.

The inputs shall be: a Tel-Page, a 600 ohm, and two high impedance inputs, strapped in parallel.

The input sensitivity required to receive full rated output shall be: Tel-Page - 50mV, 600 ohm - 0.50V, and Hi-Z - 0.50V. The input impedance shall be Tel-Page - 600 ohm, 600 ohm - 600 ohm, and Hi-Z - 10K ohm.

The front panel shall include a power indicator, power switch, peak level indicator, circuit breaker reset plunger, gain control, and be rack mounted as standard.

The back panel shall include input connectors, screw terminals, for both the Tel-Page and 600 ohm inputs, phono (RCA) connectors for both Hi-Z inputs. Output connectors shall be screw barrier

The power amplifier shall be available in either 120VAC 60Hz or 240VAC 50Hz versions (add DV to the model). The maximum power consumption of the unit shall be 720W.

The unit shall measure 19"W x 3.5"H x 11"D (48.2cm x 8.8cm x 27.9cm). The unit shall weigh, 60 watt - 17lbs (7.7kg) and 125 watt - 20lbs (9.1 kg). The unit shall include a full 7 year warranty be designed and manufactured in the United States of America.



Grommes~Precision

847-599-1799 · 800-SINCE-46 · FAX: 847-599-6178

1331 Estes Ave. · Gurnee, IL 60031 · USA

www.grommesprecision.com

Grommes~Precision